



型号	尺寸	A	B	C	D	E	F
M133		133	117.5	93.6	77	61.7	40.5
M175		175	157.5	131.5	69.5	65	44
M190		190	157.5	129.5	69.5	61	44.6
M220		220	235.5	153.9	71	65	44
M225-A		225	210.7	153.9	85	75	51
M225-B		225	210.7	153.9	99	89	62.7
M250		250	240	172	99	86	56
M280		281	260	191	112	81	52.5

Unit:mm

Impeller : Made of PA66 / Aluminum

風 輪 : 尼龙66或铝

Frame : Made of Die-cast Aluminum

外 框 : 压铸铝

Motor : External rotor & Capacitor-run induction motor

電 機 : 外转子电容运转异步电机

Model (型号)	Bearing System (轴承)	Rated Voltage (电压) [V]	Freq. (频率) [Hz]	Current (电流) [A]	Input power (功率) [W]	Speed (转速) [RPM]	Maximum Air Flow (风量) [CFM]	Maximum Air Flow (风量) [m³/h]	Max. Static Pressure (静压) [InchH ₂ O]	Max. Static Pressure (静压) [Pa]	Niose Level (噪音) [dB-A]	Mass (质量) [g]
M133HA1	Ball	115	60	0.34	35	3100	203	345	1.2	300	56	800
M133HA2	Ball	230	50	0.14	30	2600	171	290	0.72	180	51	800
M175HA1	Ball	115	60	0.45	60	3100	335	570	1.4	350	63	1000
M175HA2	Ball	230	50	0.28	51	2750	288	490	1.0	250	60	1000
M190HA1	Ball	115	60	0.75	90	2950	365	620	1.727	430	64	1200
M190HA2	Ball	230	50	0.30	65	2600	336	570	1.325	330	62	1200
M190HA3	Ball	380	50	0.15	60	2600	336	570	1.325	330	62	1200
M190HA3Ø	Ball	380	50	0.14	45	2600	336	570	1.325	330	62	1200
M220HA1	Ball	115	60	1.16	132	2800	583	990	2.249	560	75	1700
M220HA2	Ball	230	50	0.45	100	2500	524	890	1.687	420	72	1700
M225HA2-A	Ball	230	50	0.70	160	3000	683	1160	2.61	650	73	2100
M225HA3-A	Ball	380	50	0.31	160	2650	618	1050	2.05	510	70	2100
M225HA1-B	Ball	115	60	1.70	195	2900	789	1340	2.81	700	71	2350
M225HA2-B	Ball	230	50	0.65	140	2600	706	1200	2.21	550	69	2350
M250HA1	Ball	115	60	1.80	207	2900	878	1490	2.97	740	78	2700
M250HA2	Ball	230	50	0.72	152	2600	854	1450	2.33	580	75	2700
M250HA3Ø	Ball	380	50	0.41	150	2600	854	1450	2.33	580	75	2700
M280HA1	Ball	115	60	2.80	320	2650	1237	2100	3.01	750	78	2800
M280HA2	Ball	230	50	1.20	260	2550	1148	1950	2.93	730	75	2800
M280HA3	Ball	380	50	0.40	230	2550	1148	1950	2.93	730	75	2800

Above specification is only for reference and subject to change without notice.

以上数据仅供参考，如有变更恕不另行通知。